





CONTAC US:

Customer Service: +1 (786) 5847439

Sales Team: +1 (786) 8602528

Email: sales@lfsusa.store

www.lfsusa.store

About us



LFSUSA.STORE is a company specialized in the commercialization of equipment for restaurants, in addition to being representatives of manufacturers to the food industry. Our clients can experience the quality of our personalized service. Contact us and receive the necessary support so that the purchase of your food equipment is a wise investment.

We're more than just an online retailer. Since 2015, we've created an innovative, easy-to-use website to meet the purchasing needs of businesses from all over the globe. LFSUSA.STORE, The Leading Distributor of Restaurant Supplies and Equipment

We have everything your business needs to function at its best. Over the years we have expanded our selection of commercial equipment and wholesale supplies to include healthcare, educational, food, beverage, office, parts, hotel, shipping, and industrial supplies. Our focus is your convenience – order online from your laptop, desktop, or smartphone 24 hours a day, 7 days a week. Our fast shipping, low prices, and outstanding customer service make Latam Food Service the best choice to meet all of your professional and food service supply needs.



Amazing Customer Service

Our personalized customer service helps you buy what you need without mistakes!



No Hiddern Costs!

The prices you see on the site are the ones you pay for the equipment! No extra charges at delivery!



Free Shipping on All Orders

Get free shipping on all orders within the US and they'll arrive in 5-8 calendar days!



High Quality Content

We provide you with the relevant info you need to make the right purchasing decisions. Every one of our product descriptions is written by a dedicated content writer.



Latam Food Service

Atlas Air's Under Counter Refrigerators are a great, space saving addition to your restaurant or commercial kitchen. With a stainless steel exterior, bright white or stainless steel interior, forced air refrigeration system and digital thermostat microprocessor, your food products are sure to maintain consistent temperatures of 33°F to 41°F even in the busiest kitchens.



Model Numbers		AU29	AU48
	Interior Capacity (cu/ft)	6.7	11.1
	Exterior Size WxDxH (inches)	29x30 3/8x38 3/8	48x30 3/8x38 3/8
	Interior Size WxDxH (inches)	31x35 1/4x40	43x23 3/8x26 5/8
	Exterior Construction	High polished stainless steel	
	Interior Construction	Bright white powder coated aluminum	
	Shelves	1 white epoxy coated wire 2 white epoxy coated w	
Dimensions & Construction	Handle	ABS Plastic, recessed	
	Solid Door	1 Stainless Steel Door	
	Door Gasket	Tongue and groove, easy to clean & replace	
	Hinges	Stainless steel	
	Pilasters and Shelf Clips	Stainless steel	
	Floor	Rounded, coved corners	
	Casters	(2) Locking, (2	
	Temperature Range	33°F to 41°F	33°F to 41°F
	Refrigeration System	Force	
	Refrigerant	R290	R291
	Expansion Device	Capillar	
efrigeration	Defrost method	Automatic	
/stem	Compressor Type	Hermetic compressor	
	Condenser Type	Air cooled, electrostatic coated copper tube	
	Evaporator Type	Air cooled, electrostatic coated copper tube	
	Humidity control	Hot gas condensation evaporation	
	Power	115/60/1	115/60/1
	Plug	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P
ectrical System	Horse Power	1/6	1/6
	Kilowatts per 24 Hours	1//	
	Amperage	2.8	2.8
1	Shipping Dimensions	1 17	
	Shipping Weight		
ackaging &	Palletized	Yes, wood, front/back loading	
nipping Info	Material	Wood, card board, styrofoam, plastic wrap	
	UPC GTIN Latam	Food, card board, styrologin, plastic wrap	
		Precision temperature pre-set to 33°F to 41°F.	
	Digital Temperature	Adjustable set-point, temperature differential,	
igital Temperatur	Microprocessor	evaporator fan on/off cycles & air defrost cycles.	
Controller	Key Pad	Adjustable, tactile key pad	
	Screen	2" blue LCD	2" blue LCD
	Water resistant	Yes	Yes
Warranty	Compressor	5 Years	5 Years
	Parts	2 Years	2 Years
	Labor	2 Year	2 Year
ertifications	ETL sanitation (conforms to		
FI CITICACIONIS	ETE Satification (contonns to	, , , , , , , , , , , , , , , , , , ,	ocitical (00 aria Cariada)
pplication	For Commercial Kitchens (not	for residential use)	





Dimensions & Econstruction E	nterior Capacity (cu/ft) Exterior Size WxDxH (inches) nterior Size WxDxH (inches) Exterior Construction nterior Construction Shelves Handle Solid Door Door Gasket Hinges Pilasters and Shelf Clips Floor Casters Femperature Range Refrigeration System Refrigerant	14.1 61x30 3/8x38 3/8 56x23 3/8x26 5/8 High polished Bright white powde 2 white epoxy ABS Plastic 2 Stainless S Tongue and groove, e Stainles Stainles Rounded, co (2) Locking, (2 33°F to 41°F	r coated aluminum r coated wire c, recessed Steel Doors asy to clean & replace ss steel ss steel ved corners	
Dimensions & Econstruction E	Exterior Size WxDxH (inches) Interior Size WxDxH (inches) Exterior Construction Interior	56x23 3/8x26 5/8 High polished Bright white powde 2 white epoxy ABS Plastic 2 Stainless S Tongue and groove, e. Stainles Stainles Rounded, co (2) Locking, (2	67x23 3/8x26 5/8 stainless steel r coated aluminum r coated wire c, recessed Steel Doors asy to clean & replace ss steel ss steel ved corners) non-locking	
Dimensions & Construction Refrigeration System	Exterior Construction nterior Construction Shelves Handle Solid Door Door Gasket Hinges Pilasters and Shelf Clips Floor Casters Temperature Range Refrigerant	High polished Bright white powde 2 white epoxy ABS Plastic 2 Stainless S Tongue and groove, e Stainles Stainles Rounded, co (2) Locking, (2	stainless steel r coated aluminum r coated wire c, recessed Steel Doors asy to clean & replace ss steel ss steel ved corners) non-locking	
Dimensions & Construction	nterior Construction Shelves Handle Solid Door Door Gasket Hinges Pilasters and Shelf Clips Floor Casters Femperature Range Refrigerant	Bright white powde 2 white epoxy ABS Plastic 2 Stainless S Tongue and groove, e Stainles Stainles Rounded, co (2) Locking, (2	r coated aluminum r coated wire c, recessed Steel Doors asy to clean & replace ss steel ss steel ved corners) non-locking	
Dimensions & Example Construction	Shelves Handle Solid Door Door Gasket Hinges Pilasters and Shelf Clips Floor Casters Femperature Range Refrigerant	2 white epoxy ABS Plastic 2 Stainless S Tongue and groove, e Stainles Stainles Rounded, co (2) Locking, (2	c coated wire c, recessed Steel Doors asy to clean & replace ss steel ss steel ved corners) non-locking	
Refrigeration System	Handle Solid Door Door Gasket Hinges Pilasters and Shelf Clips Floor Casters Temperature Range Refrigerant	ABS Plastic 2 Stainless S Tongue and groove, e. Stainles Stainles Rounded, co (2) Locking, (2	c, recessed Steel Doors asy to clean & replace ss steel ss steel eved corners) non-locking	
Refrigeration Experiment of the second of t	Solid Door Door Gasket Hinges Pilasters and Shelf Clips Floor Casters Temperature Range Refrigeration System Refrigerant	2 Stainless S Tongue and groove, e Stainles Stainles Rounded, co (2) Locking, (2 33°F to 41°F	Steel Doors asy to clean & replace as steel as steel aved corners) non-locking	
Refrigeration Eystem	Door Gasket Hinges Pilasters and Shelf Clips Floor Casters Temperature Range Refrigeration System Refrigerant	Tongue and groove, e Stainles Stainles Rounded, co (2) Locking, (2 33°F to 41°F	asy to clean & replace ss steel ss steel ved corners) non-locking	
Refrigeration System	Hinges Pilasters and Shelf Clips Floor Casters Femperature Range Refrigeration System Refrigerant	Stainles Stainles Rounded, co (2) Locking, (2 33°F to 41°F	ss steel ss steel ved corners) non-locking	
Refrigeration System	Pilasters and Shelf Clips Floor Casters Temperature Range Refrigeration System Refrigerant	Stainles Rounded, co (2) Locking, (2 33°F to 41°F	ss steel ved corners) non-locking	
Refrigeration Eystem	Floor Casters Femperature Range Refrigeration System Refrigerant	Rounded, co (2) Locking, (2 33°F to 41°F	ved corners) non-locking	
Refrigeration Eystem	Floor Casters Femperature Range Refrigeration System Refrigerant	(2) Locking, (2 33°F to 41°F) non-locking	
Refrigeration System	Femperature Range Refrigeration System Refrigerant	(2) Locking, (2 33°F to 41°F) non-locking	
Refrigeration Eystem	Refrigeration System Refrigerant	33°F to 41°F	_	
Refrigeration Eystem	Refrigeration System Refrigerant	Force	JJ 1 10 41 F	
Refrigeration Eystem	Refrigerant			
Refrigeration System Control		R292	R293	
ystem [Expansion Device	Capillar		
ystem (E	Defrost method	Automatic		
<u>C</u> <u>E</u> -	Compressor Type	Hermetic compressor		
E	Condenser Type	Air cooled, electrostatic coated copper tube		
l l	Evaporator Type	Air cooled, electrostatic coated copper tube		
	Humidity control	Hot gas condensation evaporation		
	Power	115/60/1	115/60/1	
	Plug	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P	
	Horse Power	1/6	1/4	
1 0000	Kilowatts per 24 Hours	1,75	., .	
1 100 11	Amperage	2.8	4.2	
10.000000000000000000000000000000000000	Shipping Dimensions	2.0	11.2	
	Shipping Weight			
ackaging &	Palletized	Ves wood from	t/back loading	
ninning into	Material	Yes, wood, front/back loading Wood, card board, styrofoam, plastic wrap		
	JPC GTIN latam	vvoou, caru boaru, styroroarri, piastic Wrap		
	La ca i i i	Precision temperature pre-set to 33°F to 41°F.		
	Digital Temperature	Adjustable set-point, temperature differential,		
Nigital Tamparatura	Microprocessor	evaporator fan on/off cycles & air defrost cycles.		
Digital Temperature Controller	Key Pad	Adjustable, tactile key pad		
			<u> </u>	
	Screen Nator registant	2" blue LCD	2" blue LCD	
	Water resistant	Yes	Yes	
	Compressor	5 Years	5 Years	
Warranty	Parts	2 Years	2 Years	
	_abor2 Year2 Year			
Certifications	ETL sanitation (conforms to NSF 7 Foodservice), ETL electrical (US and Canada)			
Application F	or Commercial Kitchens (not f	for residential use)		





Model Numbers		AU29-SI	AU48-SI	
	Interior Capacity (cu/ft)	6.7	11.1	
	Exterior Size WxDxH (inches)	29x30 3/8x38 3/8	48x30 3/8x38 3/8	
	Interior Size WxDxH (inches)	31x35 1/4x40	43x23 3/8x26 5/8	
	Exterior Construction	High polished stainless steel		
	Interior Construction	Stainless steel		
Dimensions &	Shelves	1 white epoxy coated wire 2 white epoxy coated wire		
Construction	Handle	ABS Plastic, recessed		
Construction	Solid Door	1 Stainless Steel Door		
	Door Gasket	Tongue and groove, easy to clean & replace		
	Hinges	Stainless steel		
	Pilasters and Shelf Clips	Stainless steel		
	Floor	Rounded, coved corners		
	Casters	(2) Locking, (2) non-locking	
	Temperature Range	33°F to 41°F	33°F to 41°F	
	Refrigeration System	Force	ed Air	
	Refrigerant	R290	R291	
	Expansion Device	Capillary Tube		
Refrigeration	Defrost method	Automatic		
System	Compressor Type	Hermetic compressor		
	Condenser Type	Air cooled, electrostatic coated copper tube		
	Evaporator Type	Air cooled, electrostatic coated copper tube		
	Humidity control	Hot gas condensation evaporation		
	Power	115/60/1	115/60/1	
	Plug	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P	
Electrical System	Horse Power	1/6	1/6	
	Kilowatts per 24 Hours			
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Amperage	2.8	2.8	
	Shipping Dimensions			
D l 0	Shipping Weight at a M	Food Service		
Packaging &	Palletized	Yes, wood, front/back loading		
Shipping Info	Material	Wood, card board, styrofoam, plastic wrap		
	UPC GTIN			
	Digital Tapaparatura	Precision temperature pre-set to 33°F to 41°F. Adjustable set-point, temperature differential, evaporator fan on/off cycles & air defrost cycles.		
	Digital Temperature			
Digital Temperature	Microprocessor			
Controller	Key Pad	Adjustable, tactile key pad		
Controller	-	2" blue LCD	2" blue LCD	
	Screen			
Warranty	Water resistant	Yes 5 Years	Yes 5 Years	
	Compressor Parts	2 Years	2 Years	
	Labor	2 Years	2 Years	
Cortifications	ETL sanitation (conforms to NSF 7 Foodservice), ETL electrical (US and Canada)			
Certifications	ETE Samitation (comorms to NSF 7 Foodservice), ETE electrical (US and Canada)			
Application	For Commercial Kitchens (not	for residential use)		





Model Numbers		AU60-SI	AU72-SI	
	Interior Capacity (cu/ft)	14.1	16.6	
	Exterior Size WxDxH (inches)	61x30 3/8x38 3/8	72x30 3/8x38 3/8	
	Interior Size WxDxH (inches)	56x23 3/8x26 5/8	67x23 3/8x26 5/8	
	Exterior Construction	High polished stainless steel		
	Interior Construction	Stainless steel		
Dimonaiana 0	Shelves	2 white epoxy coated wire		
Dimensions & Construction	Handle	ABS Plastic, recessed		
	Solid Door	2 Stainless Steel Doors		
	Door Gasket	Tongue and groove, easy to clean & replace		
	Hinges	Stainless steel		
	Pilasters and Shelf Clips	Stainless steel		
	Floor	Rounded, coved corners		
	Casters	(2) Locking, (2		
	Temperature Range	33°F to 41°F	33°F to 41°F	
	Refrigeration System	Force	d Air	
	Refrigerant	R292	R293	
	Expansion Device	Capillar	v Tube	
Refrigeration	Defrost method	Automatic		
System	Compressor Type	Hermetic compressor		
	Condenser Type	Air cooled, electrostatic coated copper tube		
	Evaporator Type	Air cooled, electrostatic coated copper tube		
	Humidity control	Hot gas condensation evaporation		
	Power	115/60/1	115/60/1	
	Plug	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P	
Electrical System	Horse Power	1/6	1/4	
Lieutiidai System	Kilowatts per 24 Hours		,	
	Amperage	2.8	4.2	
	Shipping Dimensions			
	Shipping Weight at a M	ood Service		
Packaging &	Palletized	Yes, wood, front/back loading		
Shipping Info	Material	Wood, card board, styrofoam, plastic wrap		
	UPC GTIN		,	
		Precision temperature pre-set to 33°F to 41°F.		
	Digital Temperature	Adjustable set-point, temperature differential,		
Digital Temperature	Microprocessor	evaporator fan on/off cycles & air defrost cycles.		
Controller	Key Pad	Adjustable, tactile key pad		
	Screen	2" blue LCD	2" blue LCD	
	Water resistant	Yes	Yes	
Warranty	Compressor	5 Years	5 Years	
	Parts	2 Years	2 Years	
	Labor	2 Year	2 Year	
Certifications	ETL sanitation (conforms to NSF 7 Foodservice), ETL electrical (US and Canada)			
A mulication	For Commercial Kitchens (not for residential use)			
Application				



CONTAC US:

Customer Service

+1(786) 5847439

Sales team: +1(786) 8602528

WEB SITE: www.lfsusa.store

Email: sales@lfsusa.store