



Counter Chiller &
Freezer Collection
Pizza Cabinet

LFSUSA.STORE



KEY FEATURES

- Patented top-mounted removable independently cooling system, can be replaced with new one immediately as a whole. Interchangeable cooling system with different temperature ranges allows flexible application and easy maintenance
- The working table top is sufficient for a 12" pizza dough
- Unique airflow design with protective air curtain ensures the food in the GN pan fresh
- Patented semi frequency variable technique using electronic expansion valve controlled by VFD (variable frequency drive), can automatically adjust the operating parameters, ensuring wonderful working performance and lower energy consumption
- Automatically vaporizing defrost water, drainage is not required
- Removable door gasket, easy to replace the heaters inside
- Adjustable feet or castors upon request

●Accommodating 2/1 GN size
 ٤٥ 2/1 ج٤

●Foodsafe 304 grade stainless steel exterior and interior
 ٣٠٤ 304 ٤

●Galvanized sheet exterior back and base
 ٤ ٤ ٤ ٤

●Fitted with cylindrical lock for doors
 ٤ ٤ ٤

● 1.0 mm thick durable 304 grade stainless steel table top
 1.0mm ٣٠٤ ٤ ٤

● Accommodating 400*600mm bakery pan or GN pan
 ٤ 400*600mm ٤ ٤ ٤

OPTIONS

- 304 grade stainless steel exterior and interior back / base
- Heated film glass door
- Pass through door
- Salad plate upon request
- Wooden board under table top
- Table top extension
- 1.2mm thick 304 grade stainless steel table top
- 2,3 or 1/3+2/3 drawers bank
- Cylindrical lock for drawers
- Internal light for door type
- Lock plate
- Right-hand-side condenser unit
- Remoted type condensing unit
- Back/ side splash
- Front/side skirting
- Castors or adjustable feet
- 50 mm height skirting with louvre for sitting on plinth
- Additional shelving/trayslides for door type



PIZZA CABINET

TECHNICAL DATA



Model	PW10H	PW20HH	PW30HHH
Temp Range	-2°C ~ 4°C	-2°C ~ 4°C	-2°C ~ 4°C
Capacity(L)	216	416	656
Rating Power (W)	420	450	542
Climate Class	4/5/7		
External Dimension (mm)			
Width	1152	1815	2476
Depth	760		
Height	1050		
Internal Dimension (mm)			
Width	587	1249	1911
Depth	658		
Height	558		
Thickness of 304 Grade Stainless Steel (mm) #304			
Exterior	0.7		
Interior	0.5		
Door or drawer	0.7		
Open Depth (mm)			
Door Type	1380		
Drawer Type	1466		
GN pan			
Quantity	4 or 5	8 or 9	12
Size(mm)	325*176*150		
Maximum Loading Height of Drawer (mm Per Drawer) ㉵gōr☒☒rg			
2 Drawers	150		
3 Drawers	100		
Compressor (HP)	1/4	3/8	3/8
Refrigerant			
Type	R134a		
Standard Fitting for Door Type			
PE Coated Shelve	1	2	3
Trayslides (Pair)	1	2	3
Packing	Simple package/Carton		
Packing Size	1212*820*1250	1875*820*1250	2536*820*1250
Shipping			
Qty/20GP	22	14	8
Qty/40HQ	46	28	16

Optional Refrigerant: R290

TECHNICAL DATA



PIZZA CABINET

Model	PW10N	PW20NN	PW30NNN
Temp Range	-2°C ~ 4°C	-2°C ~ 4°C	-2°C ~ 4°C
Capacity(L)	216	416	656
Rating Power	420	450	542
Climate Class	4/5/7		
External Dimension (mm)			
Width	1152	1815	2476
Depth	760		
Height	1050		
Internal Dimension (mm)			
Width	587	1249	1911
Depth	658		
Height	558		
Thickness of 304 Grade Stainless Steel (mm) #304			
Exterior	0.7		
Interior	0.5		
Door or drawer	0.7		
Open Depth (mm)			
Door Type	1380		
Drawer Type	1466		
GN pan			
Quantity	4 or 5	8 or 9	12
Size(mm)	325*176*150		
Maximum Loading Height of Drawer (mm Per Drawer)			
2 Drawers	150		
3 Drawers	100		
Compressor (HP)	1/4	3/8	3/8
Refrigerant			
Type	R134a		
Standard Fitting for Door Type			
PE Coated Shelves	0	0	0
Trayslides (Pair)	0	0	0
Packing	Simple package/Carton		
Packing Size	1212*820*1250	1875*820*1250	2536*820*1250
Shipping			
Qty/20GP	22	14	8
Qty/40HQ	46	28	16

Optional Refrigerant: R290

**Hotel
Restaurant
Catering Equipment**



CONTACT US:

Customer Service

+1(786) 5847439

Sales team:

+1(786) 8602528

WEB SITE:

www.lfsusa.store

Email:

sales@lfsusa.store

**WHOLESALE- SWF-2
LFSUSA.STORE**